

Technical drawing of a building section showing a central room with a door and a window. The drawing includes dimensions for the room (2.69m high, 2.66m wide) and the building footprint (0.16m, 2.40m, 3.60m, 2.40m, 0.16m). The ground level is marked with elevations 33.64, 33.68, 33.70, 33.73, and 33.76. The foundation is labeled "OK Fundamente".

EDPM ziegelrot-schwarz gesprenkelt
Falschutz gemäß DIN 1176
Fallhöhe 280 cm

Plasterzelle 16/16/12 in Beton

Linierung b = 50 mm R 3,25

33,78

33,76

33,74

33,58

33,72

33,73

33,69

33,7

33,68

33,66

33,64

33,66

33,69

33,72

0,2%

1,4%

1,4%

0,2%

2

2

2

33.70

33.69

33.48

Fundamente

Fußplatte Ø 0,15

Fundament
40/40/80
C 20/25

Pflasterzeile
16/16/12
in 15 cm Beton
C 12/15

12,2 cm Kunststoffbelag für Kinderspielplätze, kritische Fallhöhe 2.80m
gem. DIN EN 1177, schüttbeschichtet, wasserdurchlässig
gemäß DIN EN 14877:2013, DIN 18035-6:2021-08 und RAL-GZ 943/3
mehrlagig aus
nm Oberschicht, EPDM-Granulat und Polyurethan ziegelrot, gesprenkelt und
110 mm Basisschicht, Gummigranulat-fasern und
Polyurethan geschüttet, Farbe schwarz

30 cm ungebundene Tragschicht 0/32
gem. DIN 18035-6

8 cm Betonpflaster 'Siliton',
4 cm Brechsand-Splitt-Gemisch 0/5
15 cm Schottertragschicht 0/32

27 cm Gesamtaufbau

42,2 cm Gesamtaufbau

