



① fitted to outside diameter item 2 at the choice of manufacturer

Integral leak rate < 1×10^{-10} mbar l/s

Outgassing rate < 5×10^{-10} mbar l/s cm²

pay attention to F-TG-QUA-de-Schweisstechnik-V007

UHV-suitable cleaning, an example can be found in the guideline F-TG-V6.1e and F-TG-V-6.3e

Details, also to the alternative materials can be found in F-DS-HEB-en-VC_0096_Detailed_Specification_Straight_Tubes

Welding classification	Quality level
DIN EN ISO 5817	
Vacuum weldings	-B-

Edges ISO 13715 $\begin{matrix} +0.3 \\ -0.1 \end{matrix}$ $\sqrt{Rz25}$

Copying of this document and giving it to others and the use of communication of the contents thereof are forbidden without express authority. Offenders are liable to the payment of damages. All rights are reserved in the event of the grant of a patent or the registration of a utility model or design.		Projection	Change Number
GS Helmholtzzentrum für Schwerionenforschung GmbH Planckstrasse 1, 64291 Darmstadt		Surfaces DIN EN ISO 1302:2002	-----Approved-----
Dimensions without tolerance indication DIN ISO 2768-1-1 DIN ISO 2768-2-1:1991 DIN EN ISO 13920-BF		Weight 21,4 kg	Scale 1:1
Drawn 07.07.2025 EHEGER	Date 07.07.2025	Name ZURKAN	Description Beamtube
Checked 07.08.2025 TEBERL	Date 07.08.2025	Name TEBERL	Size A1
Approved 22.09.2025	Date 22.09.2025	Name TEBERL	Description VC-1373326-A-V60
FR			Rev. - Sheet 1 of 1